

**SYNOPSIS**

**RECOMMENDATIONS**

**EXECUTIVE SUMMARY**

**ASSESSMENT OF THE  
VULNERABILITY OF  
THE GREAT SOUTH BAY SHORELINE  
TO TIDAL FLOODING**

*Prepared for:*

**New York Coastal Partnership  
Babylon New York**

**SYNOPSIS  
RECOMMENDATIONS  
EXECUTIVE SUMMARY**

**ASSESSMENT OF THE VULNERABILITY OF THE GREAT  
SOUTH BAY SHORELINE TO TIDAL FLOODING**

*Prepared for:*

New York Coastal Partnership  
48 Deer Park Avenue  
Babylon NY 11702

*Prepared by:*

Timothy W. Kana and Ram Krishnamohan  
Coastal Science & Engineering, Inc.  
P.O. Box 8056 Columbia SC 29202

[CSE'93-94 (726) R]  
November 1994

## PREFACE

Severe damage was done to the Long Island coastline by the northeasters of 1992 and the major storm of March 1993. These storms caused local short-term damage and disruption; however, more importantly, they raised the specter of significant economic injury to communities already experiencing the rigors of a recession. Given the downturn in defense, construction, and general economic activity, Long Island cannot afford a serious setback to its image as a great place to live and work. The response to this damage included a series of local initiatives, the formation of activists groups, and the call for all kinds of studies and hearings. The State of New York then organized the Coastal Erosion Task Force. There has, however, been very little physical work performed.

To many of us involved in the economic life of Long Island, there appeared to be one significant issue not being addressed — a rational analysis of the alternatives available and the cost of those alternatives. We need to understand the economic impact to the entire island's economy if these alternatives are not acted upon. Accordingly, the New York Coastal Partnership was formed with one mission:

**. . . to develop a true cost/benefit analysis of coastal erosion impacts . . .**

To achieve this end, we developed a methodology and focussed on a significant segment of the coastline, Fire Island. This methodology included overall scientific reviews and planning, combined with site-specific projections. The partnership commissioned two studies. The first, presented herein, is an engineering analysis of causes and mitigants of coastal erosion, including the prospect for breaching of the barrier beach.

The second study, already commenced, will provide an economic analysis of the impact of such erosion and breaches on both the mainland and the barrier islands. This study, hopefully, will also provide the cost-benefit analysis required for activation of a U.S. Army Corps of Engineers beach stabilization project and the impetus to apply the same methodology to the remainder of the Long Island coastline.

*Dan Keane, Maurice Barbash, Irving Like*  
Babylon, New York                      July 1994

## TABLE OF CONTENTS

PAGE

PREFACE

### TABLE OF CONTENTS

SYNOPSIS OF FINDINGS . . . . .	i
Recommended Plan . . . . .	ii
ACKNOWLEDGMENTS . . . . .	iii
ABOUT THE AUTHORS . . . . .	iv
EXECUTIVE SUMMARY . . . . .	v
ADDENDUM — NOVEMBER 1994 (8 pages)	
REFERENCES (6 pages)	

### [UNDER SEPARATE COVER]

1.0 Introduction . . . . .	1
2.0 Primer on Coastal Processes and Shoreline Stabilization . . . . .	4
2.1 Storms . . . . .	8
2.2 Historical Inlets . . . . .	10
2.3 Shore-Protection Projects . . . . .	11
3.0 Updated Sediment Budget for the South Shore . . . . .	14
3.1 Application to Long Island, New York . . . . .	14
3.2 Database . . . . .	14
3.2.1 Compartment Boundaries . . . . .	16
3.3 Sediment Budget Formulation . . . . .	18
3.3.1 Longshore Transport Estimate . . . . .	22
3.4 Sediment Budget Results . . . . .	24
3.4.1 Impact of Dredge and Fill Projects and Washovers . . . . .	29
3.4.2 Inlet Trapping ( $Q_c$ ) . . . . .	31
3.5 Discussion . . . . .	32
3.5.1 Inlets, Breaches, and Washovers . . . . .	35
3.5.2 Beach Fills and Groins . . . . .	36
3.6 Management Implications . . . . .	38

**TABLE OF CONTENTS**  
**(continued)**

	<b>PAGE</b>
4.0 Barrier Island Cross-Sections . . . . .	41
4.1 Westhampton Profiles . . . . .	41
4.1.1 Barrier Sediment Volumes . . . . .	46
4.2 Fire Island Profiles . . . . .	51
4.3 Sand Reservoir in Dunes for Surge Protection . . . . .	62
5.0 Storm-Surge Analysis — Existing Conditions . . . . .	69
5.1 Predicted Versus Actual Tidal Storm Surges . . . . .	70
5.2 Flooding Under Existing Conditions . . . . .	80
6.0 Scenarios of Breaches . . . . .	82
6.1 Hydraulic Controls on Tidal Surges at Inlets . . . . .	84
6.1.1 Background . . . . .	84
6.1.2 Flow Characteristics Through Existing Inlets . . . . .	85
6.1.3 Computation of Flow Characteristics . . . . .	87
6.2 Increase in Great South Bay Tidal Prisms . . . . .	93
6.3 Influence of New Inlet Formation . . . . .	93
6.4 Additional Mainland Flooding Due to Breaches . . . . .	96
7.0 Tidal Storm-Surge-Induced Damages . . . . .	99
7.1 Subdivision of the Shoreline into Reaches . . . . .	99
7.2 Computation of Damage Levels . . . . .	101
7.3 Damage Analysis and Results . . . . .	101
7.4 Summary of Damages . . . . .	106
7.5 Additional Mainland Damages Due to Barrier Breaches . . . . .	113
8.0 Requirements and Costs of Preventing Permanent Breaches . . . . .	115
8.1 Preservation of the Littoral Sand Budget . . . . .	116
8.2 Artificial Nourishment . . . . .	118
REFERENCES . . . . .	122
APPENDIX — Computer Model Results (under separate cover)	

## SYNOPSIS OF FINDINGS AND RECOMMENDATIONS

- The mainland shoreline around Great South Bay is vulnerable to storm tides and will sustain even greater damages if Fire Island and Oak Beach are breached.
- While most of Fire Island is wide, high, and not eroding fast, several sites are narrow, low, and eroding. These short, unhealthy stretches of the barrier island provide the initial conditions for breaches during a severe storm.
- History, particularly at Westhampton Beach, has proved that **initial** breaches during a storm are small and do not significantly change mainland flood levels. Existing inlets control that.
- Once formed, one or two breaches will persist and enlarge under normal tides. They become the "existing inlets" for the next storm.
- The next storm, regardless of size, will increase bay tides and mainland flooding by way of the breach inlet(s).
- The maximum potential increase in bay storm tides is about 3 feet (ft) but a more likely scenario is 1-2 ft because multiple huge breach inlets are unlikely to persist; one or two middle-sized inlets will persist. If the peak 100-year storm-tide elevation is now 6 ft at a locality, large breach inlets will potentially raise it to 8 ft.
- A 2-ft rise in Great South Bay storm-tide elevations expands the flood inundation area by roughly 25-33 percent (~4,500 acres or ~7 square miles).
- Regardless of storm intensity, the mainland flood area will increase if a breach(es) is left open and expands. This means either flooding at higher elevations for a given storm, or more frequent flooding over time for a given flood plain location.
- The impact of additional flooding on the mainland, as described in this report, is an incremental (~25 percent) increase when considered broadly over a large area. Yet for specific facilities situated at the present peak flood elevation, higher tides may force shutdowns and exponentially increase damages.
- The **additional** average annual damages due to breaches are conservatively estimated at \$15 million per year (versus ~\$60 million per year for expected damages under existing conditions).
- These additional mainland damages can be avoided by restoring and maintaining a "healthy" barrier island cross-section. The report provides specific criteria and cost estimates (Table S-1) for barrier island preservation through nourishment and related activities.
- An analysis of beach erosion shows eastern Fire Island now looks like Westhampton Beach in the 1950's because of high erosion rates, lack of nourishment, low dunes, and a narrow width. This condition is likely to shift west over the next 30 years if nothing is done.
- Central Fire Island remains stable although several localized erosion hot spots, notably Old Inlet and Water Island, need repairs to reduce the threat of a breach. Many other sections could benefit from dune enhancement after the storms of December 1992 and March 1993, but the overall condition of the central barrier is healthy.
- Western Fire Island, particularly the area from Ocean Beach to Robert Moses State Park, will erode at a faster rate in the future because of offshore changes since the 1950's.
- Western Fire Island erosion accounts for most of the sand entering Fire Island Inlet. Reducing erosion rates in this area by way of groins (one of several alternatives recommended in the report) would offer secondary benefits including reduced shoaling rates in Fire Island Inlet.

- **Recommended Plan**

- Initial nourishment — 6,000,000 cubic yards (cy) in Year 1 with 50 percent placed in each of two five-mile reaches (Moriches Inlet to Smith Point County Park and Fire Island Pines to Ocean Beach). Each of these beach fills will gradually feed areas to the west.
- Periodic renourishment at a rate averaging 500,000 cy per year beginning in Year 6 with the major portion added at the east end of Fire Island.
- Construction of sand-retaining structures (e.g., groins) along a six-mile reach from Ocean Beach to Robert Moses State Park.
- Dune enhancement, restoration at washovers, and breach closure on an episodic basis (Table S-1) where dune volumes above flood levels are lacking (criteria of Section 4.0).
- Regular shoreline monitoring to document conditions, track performance of improvements, and refine future designs.
- Periodic maintenance of Oak Beach shore-protection structures.

The report is multidisciplinary, covering the specialized fields of coastal erosion, storm-tide prediction, and shoreline flooding. Chapters cover a regional sediment budget, summaries of predicted flood elevations, estimates of damage, and alternatives for mitigation and prevention of breaches. An expanded executive summary provides an overview of study methods, findings, and implications. The main report includes detailed tables, figures, and discussions of the results.

**TABLE S-1.** Preliminary cost estimate (in current dollars) for the recommended plan over 10-, 20-, and 50-year periods, assuming all items are completed during the period of interest.

Item	Net Cost (thousands)	Frequency	Average Annual Cost (thousands)		
			10-Year	20-Year	50-Year
<i>Dune Rebuilding</i> at Washovers	250	Once in 10 years	25	25	25
<i>Dune Enhancement</i> to Storm Tide Levels	750	Once in 25 years	75	37.5	30
<i>Breach Closure</i> After Major Storms	1,000	Once in 25 years	100	50	40
<i>Beach Disposal</i> from Navigation Projects	5,000	Over 10 years	500	500	500
<i>Annual Maintenance</i> <i>Nourishment</i>	1,800	Each year after Year 6	900	1,350	1,620
<i>Sand-Trapping Structures</i> Western Fire Island	10,000	Once in 50 years	1,000	500	200
<i>Initial Nourishment</i>	40,000	Once in 50 years	4,000	2,000	800
<i>Contingency/Maintenance/</i> <i>Monitoring</i>	500	Every year	<u>500</u>	<u>500</u>	<u>500</u>
Average Annual Cost (divided by 1,000 and rounded)			<b>\$7,000</b>	<b>\$5,000</b>	<b>\$3,700</b>
Total Cost (actual — rounded)			<b>\$70,000,000</b>	<b>\$100,000,000</b>	<b>\$185,000,000</b>
Average Annual Cost (actual — rounded) per ft of Shoreline			<b>\$40/ft/yr</b>	<b>\$30/ft/yr</b>	<b>\$20/ft/yr</b>

## ADDENDUM — NOVEMBER 1994

Following completion of the present report, Coastal Science & Engineering, Inc. (CSE) was asked to prepare rough cost estimates for specific barrier-island protection schemes. These are provided below as "first-cut" approximations for discussion purposes and comparison with the expected benefits from maintaining the integrity of Fire Island.

CSE bases the cost estimates primarily on results of the updated sediment budget (Section 3.0) and profile volume analysis (Section 4.0) as well as recent history of nourishment costs in New York. However, results from analogous projects in other states are also drawn upon to insure the approaches are feasible and the unit cost estimates are realistic. Because an up-to-date shoreline survey is not available yet, the quantity estimates are based on older data. Experience has shown that even out-of-date profile surveys which confirm regional decadal trends (e.g., groin field accretion, jetty fillets, inlet trapping, etc.) will yield reasonable predictions of future changes. The profile volume approach to nourishment (Kana, 1993) also yields quantity estimates (for underwater, beach, and dune volumes) where comparative surveys are lacking.

An important variable is the unit cost of sand. For obvious reasons, accessibility and transportation distance tend to control unit costs. To simplify the cost estimates, CSE assumes nourishment from **external** (nonlittoral) sources will cost at least \$5 per cubic yard. This is similar to unit costs of sand delivery within 30,000 ft for the 1993 Gilgo/Robert Moses nourishment using sand from Fire Island Inlet and for the 1993-1994 breach closure at Westhampton Beach using an offshore borrow site (USACE—New York District, unpubl. data). Small-scale projects such as dune reshaping by bulldozers using in-situ sand or lagoon dredging with harbor dredges can be performed at much lower cost, sometimes well under \$2 per cubic yard.

For medium-to-large-scale projects, we draw on more than 20 beach restoration projects CSE has completed since the early 1980's using a variety of borrow sources and placement techniques. Performance reports from many of these projects, particularly those at Hunting Island, Myrtle Beach, and Seabrook Island (South Carolina), offer insight regarding loss rates as a function of project length and unit volumes.

An overriding assumption in CSE's estimates for Fire Island is that cross-shore changes will dwarf average annual changes. These cross-shore changes constitute the "beach cycle," whereby storms erode the upper beach but poststorm periods nearly restore the profile to average or "equilibrium" conditions. Long-term maintenance of eroding beaches and dunes, therefore, depends on sustained nourishment which replaces the **net** losses of sand over time, generally using **external** sources of sand. Emergency repairs, in contrast, are sometimes needed to accelerate the recovery of the beach and dunes soon after storms. Most emergency repairs can be



performed cost effectively using **internal** sources of sand, such as beach and dune scraping by bulldozers.

South Carolina's experience after Hurricane *Hugo* (Kana et al., 1990) illustrates these two fundamentally different approaches to beach restoration. In South Carolina, 65 miles of emergency dunes were scraped into place less than one month after *Hugo*. This \$1.5 million project cost only \$4.50 per linear foot (1989) because it simply entailed reshaping of the profile by bulldozers. Expenditures for beach nourishment in comparison were many times greater at approximately \$65 per linear foot over a length of 20 miles. Most of the post-*Hugo* nourishment projects involved placement of sand from **external** sources in an attempt to replace the net losses attributed to *Hugo*. The scale of those projects was, in turn, much smaller than a ten-year requirement for nourishment at the individual sites. Emergency dunes formed the nucleus of today's foredune along much of the impacted coast. In some reaches, however, the scraped dune quickly eroded because of a persistent sand deficit in the profile. Similar variations will occur along Fire Island depending on whether an individual reach has a sand surplus or deficit **before** a storm.

For purposes of developing a more specific plan and cost estimate for maintaining the viability of Fire Island, CSE recommends two hierarchies of need. The first is based on costs and attempts to prioritize actions that, if taken early, provide the greatest returns on investment (largely through reduced costs compared with later implementation). The second hierarchy is based on the impact of an action on the regional, decadal sediment budget. Clearly, the first hierarchy emphasizes low-cost alternatives whereas the second ranks large-volume projects highest.

#### **HIERARCHY OF NEEDS — BASED ON COSTS (Low to High)**

1) **Episodic dune rebuilding (in place) at washovers** via in-situ sand scraping where the nearshore profile volumes are "healthy" (e.g., Old Inlet 1994). *Cost range:* < \$10/ft; applies to ~25,000 ft of shoreline following the 1992-1993 storms. CSE assumes such activities will be required once per decade following major storms. *Net budget impact:* < \$250,000 / 10 years

2) **Dune enhancement via scraping/sand fencing (etc.)** using in-situ sand where dune volumes are lower than desirable and the *nearshore profile volumes are "healthy."* Goal should be to provide 10-30 cy/ft above the 25-100 year (stillwater) flood elevation over the length of the barrier island (applicable and cost effective along certain central Fire Island reaches) (see Section 4.0). *Cost range:* < \$15/ft; assume applies to ~50,000 ft of shoreline. CSE assumes this activity will be required only once per 20 years. *Net budget impact:* \$750,000 / 20 years

**3) Breach closure immediately after storms** using land-based equipment/nearby sand sources. Incipient flood-tidal deltas from breaches should be considered a primary borrow source. In-situ sand from the adjacent beach should be used to expedite closure. If monitoring confirms the littoral volume "borrowed" has a measurable adverse impact on adjacent areas, later nourishment from an external source can mitigate for the sand removed under emergency conditions. *Cost range:* < \$200/ft (limited reaches) would apply to a relatively small length of shoreline on the order of 5,000 ft. This is assumed only once per 25 years after major storms. *Net budget impact:* \$1 million / 25 years

**4) Beach disposal of sand from navigation projects.** Beach nourishment should be the designated disposal option for most navigation projects. Poor-quality sediments (muddy or contaminated) should **not** be disposed on the beach. Acceptable mud content for beach disposal is < 15 percent in most cases. Disposal should be as far as possible from inlets to reduce the tendency for sediments to recycle back to an inlet. **Additional cost** (beyond budget for the navigation project) of booster pumps (etc.) is estimated at \$2.50/cy. CSE estimates this can provide at least 33 percent of the annual maintenance nourishment requirement for Fire Island (i.e., 1 cy/ft/yr), particularly if the placement is concentrated along eastern Fire Island in connection with Moriches Inlet projects. Estimated applicable sand volume — 200,000 cy/yr. *Net budget impact:* < \$5 million / 10 years

**5) Annual maintenance nourishment for Fire Island.** CSE's estimated needs **average** 3 cy/ft/yr (500,000 cy/yr) of which a portion can be derived from routine navigation dredging (Item 4). The remainder (~2 cy/ft/yr) will have to come from other sources such as offshore deposits similar to the borrow areas used for the Westhampton breach closure and recent nourishment at Fire Island Pines, Fair Harbor, and Saltaire. Unit nourishment costs will vary principally with transportation distances. In general, maintenance nourishment should focus on hot spots and be placed as far updrift as feasible to improve longevity. CSE assumes unit construction costs will average \$5.50/cy which, when apportioned over the 165,000-ft length of Fire Island, yields total annual costs of ~\$1.8 million. CSE further assumes this level of maintenance will not be required until Year 6 if initial nourishment (Item 7) is completed in Year 1.

**6) Selectively install sand-trapping structures along western Fire Island** where there is a measurable depletion of offshore deposits and accelerated dune erosion. Groins or segmented breakwaters (the typical class of structures) should be as short as possible to allow efficient sand bypassing once the cells between structures are filled. The logical terminus of a groin field is Democrat Point; however, a detailed study of alternative groin configurations (spacing, length, crest height, and profile slope) should be conducted with the idea of minimizing the

number of sand-retaining structures. Impounded sand and a trend of accretion along compartment 161B (Democrat Point) means a field of groins could be tapered and ended well updrift of Fire Island Inlet.

Analogous for this recommendation are groins placed along bulges in the shorelines of Garden City and Debidue Island (South Carolina). In these two cases, previous inlet positions produced the initial bulge because of extra sand trapped by ebb-tidal deltas. Inlet migration and depletion of the abandoned delta shoals caused accelerated erosion several decades later. To hold the shoreline at the bulge, several groins were built at each locality. Once each cell filled to capacity, excess sand bypassed the structures (Fig. A-1).

The purpose of groins in any setting should be to reduce the rate of erosion without increasing downdrift erosion. Therefore, care is required before implementing this solution. Nevertheless, CSE believes it is a viable alternative for western Fire Island because of the clear trend of accelerating erosion from compartments 153A (Point O'Woods) to 161A (Robert Moses State Park) followed by rapid accretion in compartment 161B (Democrat Point). A strategically placed groin field along the "bulge" would provide a secondary benefit of reduced shoaling in Fire Island Inlet.

The scale of the Garden City (South Carolina) "bulge" is much smaller than the Fire Island Inlet bulge (in the vicinity of Kismet) due to differences in the scale of the inlets. Therefore, it is expected more sand-retaining structures would be required to stabilize western Fire Island. Using Westhampton Beach's groin field (where the structures were longer than necessary) as a guide, somewhat shorter structures on the order of 300 ft long, spaced about 1,500 ft apart, provide a first-cut estimate of costs. CSE assumes a field of 20 such groins would be required to stabilize an ~6-mile reach between Ocean Beach and the state park. With the installation of a field of groins, volumetric erosion rates in the protected area will decrease to a fraction of present rates. Well-constructed, rubblemound groins in this setting will cost from \$1,000 to \$2,500 per linear foot. Therefore, a field of 20 such structures would cost \$6-15 million, say \$10 million for initial planning purposes. This is assumed to be a one-time cost over 50 years.

**7) Initial nourishment for Fire Island.** CSE estimates 6 million cubic yards are presently required to restore a healthy dune/beach/underwater profile along 60,000 ft (~33 percent) of Fire Island. This nourishment is based on an estimated profile volume requirement below mean sea level (foredune to -20 ft NGVD) of about 500 cy/ft. This should be placed principally in the areas between Moriches Inlet and Smith Point County Park, and between Fire Island Pines and Ocean Beach. These two areas will feed downdrift reaches and improve

longevity of the project. Upon receipt of updated profiles, the existing unit volumes can be compared to identify reaches with the greatest sand deficit and refine the nourishment plan. The preferred sand sources are offshore deposits, testing at least as coarse as the intertidal beach sediments. Construction costs will average around \$5.50/cy based on recent experience, but CSE assumes additional soft costs (engineering, environmental impact analyses, permitting, and contingencies) will raise the price to \$6.75/cy (or \$675/ft) in the nourished areas. The net, one-time cost of initial nourishment would be ~\$40 million.

### **HIERARCHY OF NEEDS BASED ON SEDIMENT BUDGET (High to Low)**

There is often much debate over the impact of various shore-protection activities, but viewed from the perspective of sediment budget preservation, the following is clear: nourishment from an external source and maintenance of littoral transport are the primary ways of favorably impacting the sediment budget along the coast. Installation of sand fences, Christmas trees, or other low-cost alternatives yield a negligible impact on the sediment budget. The following hierarchy is based on the Fire Island Inlet to Montauk sediment budget as well as CSE's experience in similar settings.

- 1) *Restore annual beach nourishment and dredging disposal* on beaches to 1960's levels, particularly from Pikes Beach (Westhampton) to Smith Point County Park. This is considered more important than initial nourishment (#2) because it represents a long-term commitment.
- 2) Perform *initial nourishment* to achieve minimum healthy dune/beach/underwater profiles along entire Fire Island.
- 3) *Slow erosion rates along the "bulge"* of western Fire Island by means of sand-retaining structures.\*
- 4) *Close breaches and return flood tidal delta deposits* to the ocean side of breaches.
- 5) *Restore dunes in washovers.*
- 6) *Enhance dunes* mechanically to preserve the littoral budget seaward of the foredune during storms (i.e., minimize washovers).

---

\*NOTE: Retarding longshore transport in this case will produce secondary benefits through reduced shoaling in Fire Island Inlet. The effect downdrift will be a reduction in the rate of accretion at the jetty fillet of Democrat Point. The effect of short groins along western Fire Island on erosion at Gilgo Beach, if it could be quantified accurately, would be dwarfed by the regional effects of sand trapping at Fire Island Inlet, one of the largest inlets along the mid Atlantic coast.

- 7) *Plant dune grass.*  
 8) *Install sand fences, Christmas trees, etc.*

### SUMMARY OF COSTS

The above-listed barrier restoration estimates have been totaled and annualized in Table A-1 for 10-year, 20-year, and 50-year periods (in current dollars) for purposes of comparing with expected benefits. The total costs vary slightly from those given in Section 8.0 of the report because of additional items such as sand-trapping structures. Beach disposal from navigation projects reduces the annual maintenance nourishment requirement from other sources. A contingency line item provides for soft costs such as engineering, environmental protection and mitigation, repairs along Oak Island, and periodic monitoring.

**TABLE A-1.** Preliminary cost estimate (in current dollars) for the recommended plan over 10-, 20-, and 50-year periods, assuming all items are completed during the period of interest.

Item	Net Cost (thousands)	Frequency	Average Annual Cost (thousands)		
			10-Year	20-Year	50-Year
<i>Dune Rebuilding</i> at Washovers	250	Once in 10 years	25	25	25
<i>Dune Enhancement</i> to Storm Tide Levels	750	Once in 25 years	75	37.5	30
<i>Breach Closure</i> After Major Storms	1,000	Once in 25 years	100	50	40
<i>Beach Disposal</i> from Navigation Projects	5,000	Over 10 years	500	500	500
<i>Annual Maintenance</i> <i>Nourishment</i>	1,800	Each year after Year 6	900	1,350	1,620
<i>Sand-Trapping Structures</i> Western Fire Island	10,000	Once in 50 years	1,000	500	200
<i>Initial Nourishment</i>	40,000	Once in 50 years	4,000	2,000	800
<i>Contingency/Maintenance/</i> <i>Monitoring</i>	500	Every year	<u>500</u>	<u>500</u>	<u>500</u>
Average Annual Cost (divided by 1,000 and rounded)			<b>\$7,000</b>	<b>\$5,000</b>	<b>\$3,700</b>
Total Cost (actual — rounded)			<b>\$70,000,000</b>	<b>\$100,000,000</b>	<b>\$185,000,000</b>
Average Annual Cost (actual — rounded) per ft of Shoreline			<b>\$40/ft/yr</b>	<b>\$30/ft/yr</b>	<b>\$20/ft/yr</b>

**Relationship of CSE Recommendations to New York  
Governor's Coastal Erosion Task Force Recommendations\***

Issue	New York State	CSE
Inlet Sand Bypassing	Recommended for Moriches and Fire Island Inlets (among others)	Bypassing technically means excavation of an updrift beach (e.g., jetty fillet) before sand enters an inlet, and discharge along the downdrift beach. CSE supports this implicitly but believes it is often more practical to apply this by means of channel dredging (i.e., after sediments enter the inlet) and disposal along downdrift beaches. CSE also makes a case for updrift disposal (i.e., back passing) at Fire Island Inlet using inexpensive means such as trucking for small-scale projects. An updated regional sediment budget will help establish appropriate rates and schedules for bypassing and back passing.
Maintain Barrier Integrity by Filling Washovers and Breaches	<b>Recommended</b> general approach without specific criteria	<b>Recommended</b> — CSE offers specific criteria regarding unit volumes for dunes and barrier cross-sections (Section 4.0) and recommends use of nearby deposits (details in this memo).
Reserve of Funds for Emergency Response	Recommended	CSE supports, but does not specifically mention this in the report.
Erosion Monitoring	Recommended	Recommended.
Expedite Reformulation Study	Recommended	Recommend focus on an updated sediment budget and more detailed development of criteria for dune/beach restoration based on profile volumes and volumetric erosion rates.
Cost Sharing	Outlines alternatives	Not discussed.

[continued . . .]

Issue	New York State	CSE
<b>Priority Actions</b>		
a) Augment downdrift placement of sand from navigation projects	Recommended	Recommended.
b) Fill washovers	Recommended	Recommended with some specific criteria. Note: The state cost estimate appears high considering this can often be accomplished using in-situ sand.
c) Reserve fund for rapid response	Recommended	CSE supports but does not specifically recommend a fund.
<b>Long-Term Strategy (Selected Items)</b>		
a) Channel dredging; disposal on adjacent beaches	Recommended	Recommended (back passing also recommended for western Fire Island).
b) Hold shoreline position	Recommended for Coney Island, Rockaway, etc., but does not mention western Fire Island communities	Recommended for Fire Island communities and Oak Beach based on rough benefit/cost analysis with respect to potential of breach impacts along the mainland.
c) Shoreline monitoring	Recommended	Recommended.
d) Restore beach/ dunes (first costs)	Budget estimate at \$60 million	Budget estimate at \$40 million (average annual, 20-year cost estimate with renourishment is \$4.5 million per year).
e) Sand-retaining structures	Not mentioned for Fire Island	Recommended for a limited reach along western Fire Island to reduce the rate of erosion and shoaling in Fire Island Inlet.

**\*References**

- Kana, T.W., R. Krishnamohan. June 1994. Assessment of the vulnerability of the Great South Bay shoreline to tidal flooding. Final Report for New York Coastal Partnership; CSE, Columbia, SC, 127 pp. + appendices.
- Governor's Coastal Erosion Task Force. Sept. 1994. Final Report: Summary and Recommendations; Vol. 1 — Emergency Response to Coastal Storms; Vol. 2 — Long-Term Strategy. NY State Dept of State and Dept of Environmental Conservation, Albany, NY (3 vols.).

## REFERENCES

- Aero Service Corp. 1967. Planimetric maps of the south shore of Long Island. Aero Service Corp., Philadelphia, Penn., 46 plates.
- Bigelow, S.S. 1968. Bellport and Brookhaven: a saga of the sibling hamlets at Old Purchase South. Bellport-Brookhaven Historical Society, Bellport, N.Y., 126 pp.
- Bokuniewicz, H. 1981. The seasonal beach at Easthampton, New York. *Shore & Beach*, Vol. 49(3), pp. 28-33.
- Bokuniewicz, H., and S. Tangren. 1985. Volume requirements for the subaerial beach at Easthampton, New York. *Shore & Beach*, Vol. 53(1), pp. 16-18.
- Bokuniewicz, H., and J. Tanski. 1991. Development of a coastal erosion monitoring program for the south shore of Long Island, New York. Proc. Workshop for Long Island Regional Planning Board, SUNY Stony Brook, N.Y., 67 pp.
- Boothroyd, J.C., and D.K. Hubbard. 1975. Genesis of bedforms in mesotidal estuaries. In J.E. Cronin (ed.), *Estuarine Research*, Vol. 2, Geology and Engineering, Academic Press, N.Y., pp. 217-234.
- Bruun, P. 1962. Sea-level rise as a cause of shore erosion. *Jour. Waterways and Harbor Div.*, ASCE, New York, N.Y., Vol. 88(WW1), pp. 117-132.
- Bruun, P. and F. Gerritsen. 1961. Stability of coastal inlets. In Proc. 7<sup>th</sup> Conf. Coastal Engineering, ASCE, New York, N.Y., pp. 386-417.
- CERC. 1984. *Shore Protection Manual*. Vol. I and Vol. II., U.S. Army Corps of Engineers, Coastal Engineering Research Center, Ft. Belvoir, Vir.; U.S. Government Printing Office, Washington, D.C.
- CSE. 1993. Assessment of the vulnerability of the Great South Bay shoreline to tidal flooding. Proposal No. CSE'93 P-15, Coastal Science & Engineering, Inc., Columbia, S.C.
- Cashin Assoc. 1993. The environmental impacts of barrier island breaching with particular focus on the south shore of Long Island, New York. Prepared for N.Y. State Dept. of State, Albany, 44 pp.
- Chow, V.T. 1959. *Open Channel Hydraulics*. McGraw-Hill, New York.
- Colony, R.J. 1932. Source of the sand on the south of Long Island and the coast of New Jersey. *Jour. Sed. Petrol.*, Vol. 3(3), pp. 150-159.
- Czerniak, M.T. 1976. Engineering concepts and environmental assessment for the stabilization and sand bypassing of Moriches Inlet, New York. TetraTech Rept. to U.S. Army Corps of Eng., New York, N.Y., 102 pp. + app.
- DeWall, A. 1979. Beach changes at Westhampton Beach, New York, 1962-1973. Misc. Rept. 79-5, USACE, Coastal Engineering Research Center, Ft. Belvoir, Vir., 129 pp.
- Dewberry & Davis. 1989. Basis of assessment procedures for dune erosion in coastal flood insurance studies. Prepared for FEMA; Dewberry & Davis, Inc., Fairfax, Vir., 57 pp. + appendices.
- Dolan, R., F. Anders, and S. Kimball. 1985. *National Atlas of the United States of America: Coastal Erosion and Accretion*. U.S. Geological Survey National Atlas.
- Douglass, S.L. 1985. Coastal response to navigation structures at Murrells Inlet, S.C. CERC Report 85-8, U.S. Army Corps of Engineers, Vicksburg, Miss.



- Duane, D.B., D.J.P. Swift, and O. Pilkey. 1972. Linear shoals on the Atlantic inner continental shelf, Florida to Long Island. In *Shelf Sediment Transport*, Dowden, Hutchinson and Ross, Inc., Stroudsburg, Penn., pp. 447-498.
- Escoffier, F.F. 1987. Hydraulics and stability of tidal inlets. GITI Rept. No. 13, USACE, Waterways Experiment Station, Vicksburg, Miss.
- FEMA. 1987a. Flood Insurance Study, Village of Amityville, Suffolk County, New York. Federal Emergency Management Agency, Washington, D.C. (unpublished).
- FEMA. 1987b. Flood Insurance Study, Town of Babylon, Suffolk County, New York. Federal Emergency Management Agency, Washington, D.C. (unpublished).
- FEMA. 1987c. Flood Insurance Study, Village of Babylon, Suffolk County, New York. Federal Emergency Management Agency, Washington, D.C. (unpublished).
- FEMA. 1987d. Flood Insurance Study, Village of Bellport, Suffolk County, New York. Federal Emergency Management Agency, Washington, D.C. (unpublished).
- FEMA. 1987e. Flood Insurance Study, Town of Brookhaven, Suffolk County, New York. Federal Emergency Management Agency, Washington, D.C. (unpublished).
- FEMA. 1987f. Flood Insurance Study, Town of Islip, Suffolk County, New York. Federal Emergency Management Agency, Washington, D.C. (unpublished).
- FEMA. 1987g. Flood Insurance Study, Village of Patchogue, Suffolk County, New York. Federal Emergency Management Agency, Washington, D.C. (unpublished).
- FEMA. 1987h. Flood Insurance Study, Village of Westhampton Beach, Suffolk County, New York. Federal Emergency Management Agency, Washington, D.C. (unpublished).
- Flint, R.F. 1971. *Glacial and Quaternary Geology*. John Wiley & Sons, New York, N.Y., 892 pp.
- GCETF. 1993. Vol. 2. Long-term strategy. Draft Final Report, Governor's Coastal Erosion Task Force, Department of Environmental Conservation and Department of State, Albany, N.Y., 186 pp.
- Hands, E.B. 1981. Predicting adjustments in shore and offshore sand profiles on the Great Lakes. CETA No. 81-4, USACE-CERC, Fort Belvoir, Vir., 25 pp.
- Harris, D.L. 1972. Characteristics of wave records in the coastal zone. In *Wave on Beaches and Resulting Sediment Transport*, Academic Press, New York.
- Hayes, M.O. 1967. Hurricanes as geological agents: case studies of Hurricanes *Carla*, 1961, and *Cindy*, 1963. Rept. Invest. No. 61, Bur. Econ. Geol., Univ. Texas, Austin, 54 pp.
- Hayes, M.O. 1971. Geomorphology of tidal inlets, the estuarine environment. In J.R. Schubel (ed.), *Estuaries and Estuarine Sedimentation*, Amer. Geol. Inst. Short Course, pp. XIII-1 through XIII-17.
- Hayes, M.O. 1979. Barrier island morphology as a function of tidal and wave regime. In S. Leatherman (ed.), *Barrier Islands*, Academic Press, New York, N.Y., pp. 1-26.
- Hayes, M.O., and J.C. Boothroyd. 1969. Storms as modifying agents in the coastal environment. In *Guidebook Coastal Environments of NE Massachusetts and New Hampshire: Eastern Section*. Reprinted in R.A. Davis (ed.), *Beach and Nearshore Sediments and Processes*. SEPM Reprint Series No. 12, Tulsa, Okla., pp. 25-39.

- Hayes, M.O., and T.W. Kana (eds.). 1976. *Terrigenous Clastic Depositional Environments*, Tech. Rept. No. 11-CRD, Univ. South Carolina, Columbia, 306 pp.
- Hicks, S.D., H.A. DeBaugh, Jr., and L.E. Hickman, Jr. 1983. *Sea Level Variation for the United States: 1855-1980*. Tech. Rept., Tides and Water Levels Branch, National Ocean Service, U.S. Dept. Commerce, Wash., D.C., 170 pp.
- Ho, F.P., R.W. Schwerdt, and H.V. Goodyear. 1975. Some climatological characteristics of hurricanes and tropical storms, Gulf and East Coasts of the United States. NOAA Tech. Rept. NWS 15, Baltimore, Md., 87 pp.
- Jarrett, J.T. 1976. Tidal prism-inlet area relationships. GITI Rept. No. 3, U.S. Army Engineer WES, Vicksburg, Miss., 76 pp.
- Jarrett, J.T. 1977. Sediment budget analysis, Wrightsville Beach to Kure Beach, N.C. *In Proc. Coastal Sediments '77*, ASCE, New York, N.Y., pp. 986-1005.
- Jones, C.P., and A.J. Mehta. 1978. Ponce de Leon Inlet glossary of inlets report no. 6. Florida Sea Grant Program, Rept. No. 23, Gainesville.
- Kaczorowski, R. 1972. Offset tidal inlets, Long Island, New York. Unpubl. M.S. Thesis, University of Massachusetts, Amherst, 151 pp.
- Kana, T.W. (in review) A mesoscale sediment budget for Long Island, New York. Submitted to Marine Geology, manuscript, 20 pp.
- Kana, T.W., and F.D. Stevens. 1992. Coastal geomorphology and sand budgets applied to beach nourishment. In S.A. Hughes (ed.), *Proc. Coastal Engineering Practice '92*, ASCE, New York, N.Y., pp. 29-44.
- Kana, T.W., M.O. Hayes, and S.A. Covell. 1981. Fire Island to Montauk Point, Long Island, New York, reformulation study: sediment budget — phase I, Moriches Inlet. Report for N.Y. District, USACE, Contr. DACW51-81-C-0030; Research Planning Inst., Inc., Columbia, S.C., 82 pp.
- Kana, T.W., F.D. Stevens, and G. Lennon. 1990. Beach and dune restoration following *Hugo*. *Jour. of the American Shore & Beach Preservation Association, Shore & Beach*, Vol. 58, No. 4, pp. 57-63.
- Keulegan, G.H. 1967. Tidal flow in entrances: water level fluctuations of basins in communication with seas. U.S. Army Corps of Engineers, Tech. Bull. 14, Committee on Tidal Hydraulics, Wash., D.C.
- Krinsley, D.H., T. Tapavashi, M.L. Silberman, and W.S. Newman. 1964. Transportation of sand grains along the Atlantic shore of Long Island, New York, an application of electron microscopy. *Marine Geology*, Vol. 2, pp. 100-120.
- LIRPB. 1984. Hurricane Damage Mitigation Plan for the South Shore of Nassau and Suffolk Counties, New York. Long Island Regional Planning Board, Hauppauge, N.Y., 196 pp.
- LIRPB. 1989. Proposed Long Island south shore hazard management program. Long Island Regional Planning Board, Hauppauge, N.Y.
- LIRPB. 1991. Design of a Long Island south shore erosion monitoring program. Long Island Regional Planning Board, Hauppauge, N.Y., 20 pp.
- LIRPB. 1994. South shore mainland hazard management program. Draft Report (in press), Long Island Regional Planning Board, Hauppauge, N.Y.

- Leatherman, S.P. 1977. Barrier island dynamics: overwash processes and eolian transport. *In Proc. 15<sup>th</sup> Intl. Coastal Engineering Conf.*, ASCE, New York, N.Y., pp. 1958-1974.
- Leatherman, S.P. 1985. Geomorphic and stratigraphic analysis of Fire Island, New York. *Marine Geology*, Vol. 63, pp. 173-195.
- Leatherman, S.P., and J.R. Allen (eds.). 1985. Geomorphic analysis of the south shore barriers of Long Island, New York. Tech. Rept., National Park Service, Boston, Mass., 350 pp.
- Leatherman, S.P., and D.C. Joneja. 1980. Geomorphic analysis of south shore barriers, Long Island, New York: phase I. Final Report. NPS, Cooperative Research Unit, The Environmental Inst., University of Massachusetts at Amherst, 168 pp.
- McBride, R.A., and T.F. Moslow. 1991. Origin, evolution and distribution of shoreface sand ridges, Atlantic inner shelf, U.S.A. *Marine Geology*, Vol. 97, pp. 57-85.
- McCormick, C.L. 1973. Probable causes of shoreline recession and advance on the south shore of eastern Long Island. *In Coastal Geomorphology*, D.R. Coates (ed.), pp. 61-71.
- McCormick, C.L., and M.A. Toscano. 1981. Origin of the barrier island system of Long Island, N.Y. *Northeast Geology*, Vol. 3, pp. 230-234.
- NOAA. 1993. *Tide Tables: East Coast of North and South America Including Greenland*. U.S. Dept. Commerce, National Oceanic & Atmospheric Administration, National Ocean Service, Rockville, Md.
- Nersessian, G.K., N.C. Kraus, and F.C. Carson. 1993. Functioning of groins at Westhampton Beach, Long Island, New York. *In Proc. 23<sup>rd</sup> Intl. Conf. Coastal Engineering*, ASCE, N.Y., preprint, 14 pp.
- O'Brien, M.P. 1971. Notes on tidal inlets on sandy shores. Univ. Calif. Hyd. Engr. Lab., Rept. HEL 24-5, Berkeley.
- O'Brien, M.P. 1976. Notes on tidal inlets on sandy shores. GITI Rept. No. 5, Coastal Engineering Research Center, USACE, Ft. Belvoir, Vir., 26 pp.
- O'Brien, M.P., and R.G. Dean. 1972. Hydraulics and sedimentary stability of coastal inlets. *In Proc. 13<sup>th</sup> Intl. Coastal Engineering Conf.*, ASCE, New York, N.Y., pp. 761-780.
- Panuzio, F.L. 1969. The Atlantic Coast of Long Island. *In Proc. 11<sup>th</sup> Coastal Engineering Conf.*, ASCE, New York, N.Y., pp. 1222-1241.
- Pritchard, D.W., and J. DiLorenzo. 1985. Assessment of the Effects of Inlet Geometry on Currents in Moriches Inlet and on Tidal Range and Storm Surge in Moriches Bay. Marine Sciences Research Center, State University of New York, Stony Brook.
- Purpura, J.A., and T.Y. Chiu. 1977. Second report on the performance of the Ponce de Leon Inlet, Florida, improvement system. Rept. UFL/COEL-77/004, Coastal & Ocean Engineering Lab., Univ. Florida, Gainesville.
- RPI. 1985. Fire Island Inlet to Montauk Point, Long Island, New York: sediment budget analysis. Summary Report for New York District, USACE; Research Planning Inst., Inc., Columbia, S.C., 85 pp. + app.
- Rhodes, P.E. 1990. Federal emergency work on South Carolina beaches following Hurricane *Hugo*. *In Proc. Third Beach Preservation Tech. Conf.*, Florida Shore & Beach Assoc., Tallahassee, Fla., pp. 26-35.
- Sanders, J.E., and N. Kumar. 1975. Evidence of shoreface retreat and in-place drowning during Holocene submergence of barriers: continental shelf off Fire Island, N.Y. *Geol. Soc. Amer. Bull.*, Vol. 86, pp. 65-76.

- Saville, T. 1961. Sand transfer, beach control, and inlet improvements, Fire Island Inlet to Jones Beach, New York. *In Proc. 7<sup>th</sup> Conference on Coastal Engineering*, J.W. Johnson (ed.), Vol. 2, Chap. 44, pp. 785-807.
- Schwartz, R.K. 1975. Nature and genesis of some storm washover deposits. Tech. Memo. No. 61, Coastal Engineering Research Center, U.S. Army Corps of Engineers, Ft. Belvoir, Vir., 70 pp.
- Shipp, R.K. 1980. The longshore bar system of eastern Long Island, N.Y. Unpubl. M.S. Thesis, Dept. Geol., University of South Carolina, Columbia.
- Speck, S.W. 1984. Repair and restoration of beaches/dunes. Memorandum Report for FEMA; Dewberry & Davis, Inc., Washington, D.C.
- Suffolk County Planning Department. 1985. Analysis of dredging and spoil dispersal activity conducted by Suffolk County. County of Suffolk, Hauppauge, N.Y., 85 pp.
- TAW. 1985. Guidelines for the evaluation of safety of dunes as coastal defense. Unauthorized translation of Leidraad voor de beoordeling van de verligheid van duinen als zeewering, Technical Advisory Committee on Sea Defenses (Technische Adviescommissie naar de water keringen), Dutch Government Printing Office, 16 pp.
- Taney, N.E. 1961. Geomorphology of the south shore of Long Island, New York. TM No. 128, U.S. Army Corps of Engineers, Beach Erosion Board, Washington, D.C.
- Tanski, J. 1993. Unpublished data on Long Island beaches. SUNY, State University of New York, Stony Brook.
- TopoMetrics, Inc. (various dates). Unpublished flood observation records for storms in 1938, 1950, 1954, 1960, and 1962. Prepared for U.S. Army Corps of Engineers, New York District.
- TopoMetrics, Inc. 1979. Flood inundation maps and high water marks. Prepared for U.S. Army Corps of Engineers, New York District, Hauppauge, N.Y.
- URS. 1982. Existing conditions: final damage study for the Fire Island Inlet to Montauk Point damage study. Final Rept., URS Consultants, Paramus, New Jersey.
- USACE. 1958. Atlantic Coast of Long Island, New York (Fire Island Inlet to Montauk Point). Cooperative Beach Erosion Control and Interim Hurricane Study. Appendices, U.S. Army Corps of Engineers, New York.
- USACE. 1963a. Report on Operation Five High disaster recovery operations from 6-8 March 1962 storm. U.S. Army Corps of Engineers, North Atlantic Division, Civil Works Branch.
- USACE. 1963b. Fire Island Inlet to Montauk Point, Long Island, New York: general design memorandum no. 1, Moriches Inlet to Shinnecock Reach. U.S. Army Corps of Engineers, New York District, 52 pp. + app.
- USACE. 1967. Atlantic Coast of Long Island, New York, beach erosion control report — Fire Island to Montauk Point. U.S. Army Corps of Engineers, House Document No. 191, Supt. Documents, Wash., D.C., 119 pp.
- USACE. 1971. *National Shoreline Study*. U.S. Army Corps of Engineers, Multiple Volumes, Washington, D.C.
- USACE. 1980. Fire Island Inlet to Montauk Point, Long Island, New York: beach erosion control and hurricane protection project. U.S. Army Corps of Engineers, New York District, Suppl. No. 2 to GDM No. 1.
- USGPO. 1993. *Economic Indicators*. U.S. Government Printing Office, Washington, D.C.
- Van de Graaff, J. 1986. Probabilistic design of dunes; an example from The Netherlands. *Coastal Engineering*, Vol. 9, pp. 479-500.

- Vogel, M.J., and T.W. Kana. 1985. Sedimentation patterns in a tidal inlet system, Moriches Inlet, New York. *In Proc. 19<sup>th</sup> Intl. Coastal Engineering Conf., ASCE, New York, N.Y., pp. 3017-3033.*
- Walton, T.L., and W.D. Adams. 1976. Capacity of inlet outer bars to store sand. 14<sup>th</sup> Coastal Engineering Conf., ASCE, New York, N.Y., pp. 1919-1937.
- Williams, S.J. 1976. Geomorphology, shallow bottom structure and sediments of the Atlantic inner continental shelf off Long Island, N.Y. Tech. Paper No. 76-2, USACE, Ft. Belvoir, Vir., 123 pp.
- Williams, S.J., and E.P. Meisburger. 1987. Sand sources for the transgressive barrier coast of Long Island, New York: evidence for landward transport of shelf sediments. *In Proc. Coastal Sediments '87, ASCE, New York, N.Y., pp. 1517-1532.*
- Wilson, R.R., K-C. Wong, and H.H. Carter. 1991. Aspects of circulation and exchange in Great South Bay. In J.R. Schubel et al. (eds.), *The Great South Bay*, State Univ. of New York Press, Albany, pp. 9-21.
- Wolff, M.P. 1982. Evidence for onshore sand transfer along the south shore of Long Island, New York, and its implications against the Bruun rule. *Northeastern Geology*, Vol. 4(1), pp. 10-16.
- Wright, L.D., and A.D. Short. 1983. Morphodynamics of beaches and surf zones in Australia. In P.D. Komar (ed.), *Handbook of Coastal Processes and Erosion*, CRC Press, pp. 35-64.